

# SIEMENS

## Product data sheet

**6ES7322-1BH01-0AA0**


SIMATIC S7-300, DIGITAL OUTPUT SM 322,  
OPTICALLY ISOLATED, 16 DO, 24V DC,  
0.5A,  
1 X 20 PIN SUM OF OUTPUT CURRENTS  
4A/GROUP (8A/MODULE)

Supply voltage	
Load voltage L+	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	80 mA
from backplane bus 5 V DC, max.	80 mA
Power losses	
Power loss, typ.	4.9 W
Digital outputs	
Number/binary outputs	16
Limitation of inductive shutdown voltage to	L+ (-53 V)
Lamp load, max.	5 W
Load resistance range	

lower limit	48 $\Omega$
upper limit	4 k $\Omega$
<b>Output voltage</b>	
for signal "1", min.	L+ (-0.8 V)
<b>Output current</b>	
for signal "1" rated value	0.5 A
for signal "1" permissible range for 0 to 40 °C, max.	0.6 A
for signal "1" minimum load current	5 mA
for signal "0" residual current, max.	0.5 mA
<b>Switching frequency</b>	
with resistive load, max.	100 Hz
with inductive load, max.	0.5 Hz
on lamp load, max.	10 Hz
<b>Aggregate current of outputs (per group)</b>	
<b>horizontal installation</b>	
up to 40 °C, max.	4 A
up to 60 °C, max.	3 A
<b>vertical installation</b>	
up to 40 °C, max.	2 A
<b>Cable length</b>	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
Diagnostic alarm	No
<b>Diagnostic messages</b>	
Diagnostics	No
Wire break	No
Short circuit	No
Fuse blown	No
Missing load voltage	No
<b>Diagnostics indication LED</b>	
Rated load voltage PWR (green)	No

Fuse OK FSG (green)	No
<b>Galvanic isolation</b>	
<b>Galvanic isolation digital outputs</b>	
between the channels, in groups of	8
between the channels and the backplane bus	Yes ; Optocoupler
<b>Isolation</b>	
Isolation checked with	500 V DC
<b>Connection method</b>	
required front connector	20-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weight</b>	
Weight, approx.	190 g
Status	Jul 17, 2012