

SIEMENS

Product data sheet

6ES7323-1BH01-0AA0


SIMATIC S7-300, DIGITAL MODULE SM 323,
OPTICALLY ISOLATED, 8 DI AND 8 DO,
24V DC, 0.5A AGGREGATE CURRENT 2A,
1X20 PIN

Supply voltage	
Load voltage L+	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	40 mA
from backplane bus 5 V DC, max.	40 mA
Power losses	
Power loss, typ.	3.5 W
Digital inputs	
Number/binary inputs	8
Input characteristic curve acc. to IEC 61131, Type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	

up to 40 °C, max.	8
up to 60 °C, max.	8
Input voltage	
Type of input voltage	DC
Rated value, DC	24 V
for signal "0"	-30 to +5 V
for signal "1"	13 to 30 V
Input current	
for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
at "0" to "1", min.	1.2 ms
at "0" to "1", max.	4.8 ms
at "1" to "0", min.	1.2 ms
at "1" to "0", max.	4.8 ms
Cable length	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
Digital outputs	
Number/binary outputs	8
Functionality/short-circuit strength	Yes ; Electronic
Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Lamp load, max.	5 W
Controlling a digital input	Yes
Load resistance range	
lower limit	48 Ω
upper limit	4 kΩ
Output voltage	
for signal "1", min.	L+ (-0.8 V)
Output current	
for signal "1" rated value	0.5 A
for signal "1" permissible range for 0 to 60 °C, min.	5 mA

for signal "1" permissible range for 0 to 60 °C, max.	0.6 A
for signal "1" minimum load current	5 mA
for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
"0" to "1", max.	100 µs
"1" to "0", max.	500 µs
Parallel switching of 2 outputs	
for increased power	No
for redundant control of a load	Yes ; only outputs of the same group
Switching frequency	
with resistive load, max.	100 Hz
with inductive load, max.	0.5 Hz
on lamp load, max.	10 Hz
Aggregate current of outputs (per group)	
horizontal installation	
up to 40 °C, max.	4 A
up to 60 °C, max.	4 A
Cable length	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
Encoder	
Connectable encoders	
2-wire sensor	Yes
Permissible quiescent current (2-wire sensor), max.	2 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Alarms	
Alarms	No
Diagnostic messages	
Diagnostic functions	No

Diagnostics indication LED	
Status indicator digital output (green)	Yes
Status indicator digital input (green)	Yes
Galvanic isolation	
Galvanic isolation digital inputs	
between the channels	Yes
between the channels, in groups of	8
between the channels and the backplane bus	Yes ; Optocoupler
Galvanic isolation digital outputs	
between the channels	Yes
between the channels, in groups of	8
between the channels and the backplane bus	Yes ; Optocoupler
Permissible potential difference	
between different circuits	75 VDC / 60 VAC
Isolation	
Isolation checked with	500 V DC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weight	
Weight, approx.	220 g
Status	Jul 17, 2012