



SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED 16DO, RELAY CONTACTS, 1 X 20 PIN

Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	120 V
Load voltage L1	
• Rated value (AC)	230 V
Input current	
from backplane bus 5 V DC, max.	100 mA
Power losses	
Power loss, typ.	4.5 W
Digital outputs	
Number of digital outputs	16; Relays
Switching capacity of the outputs	
• on lamp load, max.	50 W; 230 V AC
Output current	
• for signal "1" rated value	2 A
• for signal "1" minimum load current	10 mA
Switching frequency	
• with resistive load, max.	1 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
• mechanical, max.	10 Hz
horizontal installation	
— up to 60 °C, max.	8 A

vertical installation	
— up to 40 °C, max.	8 A
Relay outputs	
• Rated input voltage of relay coil L+ (DC)	24 V
• Number of operating cycles, max.	100 000; 50000 (24 V DC, at 2 A); 700000 (120 V AC, at 2 A); 100000 (230 V AC, at 2 A)
Switching capacity of contacts	
— with inductive load, max.	2 A; 2 A (230 V AC), 2 A (24 V DC)
— with resistive load, max.	2 A; 2 A (230 V AC), 2 A (24 V DC)
Cable length	
• shielded, max.	1 000 m
• Unshielded, max.	600 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	No
Diagnostic messages	
• Diagnostics	No
• Wire break	No
• Short circuit	No
• Fuse blown	No
• Missing load voltage	No
Diagnostics indication LED	
• Rated load voltage PWR (green)	No
• Fuse OK FSG (green)	No
Potential separation	
Potential separation digital outputs	
• between the channels, in groups of	8
• between the channels and the backplane bus	Yes; Optocoupler
Isolation	
Isolation checked with	1500 V AC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	250 g
last modified:	23.04.2015